

# TECHNICAL DATASHEET

## ON-DEMAND MANUFACTURING 1PURB55MAT/ALCW

Conveyor belt TPU Polyurethane WHITE  
Complies with EU regulations for conveying foodstuff

### DESCRIPTION

<b>1</b>	1-ply polyester fabric
<b>PUR</b>	TPU Polyurethane
<b>B</b>	Colour: white
<b>55</b>	Top cover thickness: 0,55 mm
<b>MAT</b>	Matte finish
<b>A</b>	revAccess
<b>LC</b>	115N/mm fabric, rigid in weft, antistatic
<b>W</b>	Impregnated bottomside

### MAIN TECHNICAL DATA

**Top cover:** Hardness 85 ShA Smooth, matte  
**Total thickness:** 1,15 mm  $\pm 0,1$  mm per ply  
**Weight per m<sup>2</sup>:** 1 250 g  $\pm 10\%$   
**Manufacturing width:** 2 000 mm  
**Product temperature:** -40°C to +90°C  
**Ambient temperature:** -25°C to +60°C  
**Type of support:** Slider bed -  
**Coefficient of friction (on steel slider bed):** 0,20  $\pm 20\%$


### MECHANICAL STRENGTHS

Tolerances: -10% +20%

**Tensile strength:** 90 N/mm  
**Tensile force for 1% elongation (k1%):** 6 N/mm  
**Maximum working tension:** 10 N/mm

### MINIMUM PULLEY DIAMETERS

(at 20°C ambient temperature)




Working conditions:

- from 0°C to +8°C: add +50% on min. pulley diameter
- from -25°C to 0°C: add +100% on min. pulley diameter

The minimum pulley diameter is not related to the diameter needed to achieve a friction drive.

### SPLICING OPTIONS

DS  
Round finger single  
splice 50 x 20 mm



### PRESS SETTINGS

*These recommendations may vary according to the equipment and press heating system.*

Top heating platen ( $\pm 10^\circ\text{C}$ ): 150°C  
 Bottom heating platen ( $\pm 10^\circ\text{C}$ ): 130°C  
 Welding Time ( $\pm 1$  min): 1 min  
 Pressure ( $\pm 0,5$  bar): 1,0 bar  
 Reveyron does not recommend using foil for splicing.

### FASTENERS / LACING

Securi-P1 (inox, flat wires) - SL00 (inox, self-lock) -

### BELT FABRICATION

None

These data may change. The client remains liable for the proper choice of the belt material.  
 Reveyron cannot be held responsible for any damage caused by improper use of the belt material.

**REVEYRON SAS** 247 route du Mas Rillier - Les Echets - 01700 MIRIBEL - FRANCE  
**Light Conveyor Belts & Belt Bend Conveyors**

Tel: +33 4 78 91 08 51 [www.reveyron.com](http://www.reveyron.com) [info@reveyron.com](mailto:info@reveyron.com)

VAT FR54 769 201 187 art 286 ter du CGI - Capital 1 000 000 € - Siret 769 201 187 00010 - NAF 1396Z