

TECHNICAL DATASHEET

STANDARD RANGE 1PURXD30/EW

Conveyor belt TPU Polyurethane BLUE
Complies with EU regulations for conveying foodstuff

DESCRIPTION

1	1 ply polyester fabric
PUR	TPU Polyurethane
X	Colour: blue RAL 5015
D	Diamond pattern on running side
30	Top cover thickness: 0,30 mm
E	80 N/mm fabric, rigid in weft
W	Impregnated bottomside

MAIN TECHNICAL DATA

Top cover: Hardness 85 ShA diamond profile
Total thickness: 1,00 mm $\pm 0,1$ mm per ply
Weight per m²: 820 g $\pm 10\%$
Manufacturing width: 2 000 mm
Product temperature: -40°C to +90°C
Ambient temperature: -25°C to +60°C
Type of support: Slider bed -
Coefficient of friction (on steel slider bed): 0,20 $\pm 20\%$


MECHANICAL STRENGTHS

Tolerances: -10% +20%

Tensile strength: 60 N/mm
Tensile force for 1% elongation (k1%): 5 N/mm
Maximum working tension: 8 N/mm

MINIMUM PULLEY DIAMETERS

(at 20°C ambient temperature)




Working conditions:

- from 0°C to +8°C: add +50% on min. pulley diameter
- from -25°C to 0°C: add +100% on min. pulley diameter


The minimum pulley diameter is not related to the diameter needed to achieve a friction drive.

SPLICING OPTIONS

DS
Round finger single
splice 50 x 20 mm



DSP
Narrow single finger
splice 70 x 10 mm



PRESS SETTINGS

These recommendations may vary according to the equipment and press heating system.

Top heating platen ($\pm 10^\circ\text{C}$): 170°C
 Bottom heating platen ($\pm 10^\circ\text{C}$): 155°C
 Welding Time (± 1 min): 1 min
 Pressure ($\pm 0,5$ bar): 1,0 bar
 Reveyron does not recommend using foil for splicing.

FASTENERS / LACING

AZ5 (plastic zip) - SL00 (inox, self-lock) -

BELT FABRICATION

None

These data may change. The client remains liable for the proper choice of the belt material.
 Reveyron cannot be held responsible for any damage caused by improper use of the belt material.

REVEYRON SAS 247 route du Mas Rillier - Les Echets - 01700 MIRIBEL - FRANCE
Light Conveyor Belts & Belt Bend Conveyors

Tel: +33 4 78 91 08 51 www.reveyron.com info@reveyron.com

VAT FR54 769 201 187 art 286 ter du CGI - Capital 1 000 000 € - Siret 769 201 187 00010 - NAF 1396Z