TECHNICAL DATA SHEET



Validation date: 06/11/2014

CUSTOMIZED MANUFACTURING 2PURX30/LHR

CONVEYOR BELT TPU BLUE

Complies with FDA and EU regulations for conveying of foodstuff

CONSTRUCTION

2 2-ply polyester fabricPUR TPU polyurethan

X Colour : blue RAL 501530 Top cover thickness : 0,35 mm

L 115 N/mm fabric, rigid in weft

HR "Rice grain" positive pattern, easy to clean

MAIN TECHNICAL DATA

Top cover: hardness: 92 Sh.A surface: mat, smooth

Total thickness: 2,30 mm \pm 0,1 mm per ply

Weight per m²: $2 650 \text{ g} \pm 10\%$ Friction Coefficient on steel slider bed: $0,50 \pm 20\%$

Manufacturing width: 2 000 mm

Temperatures:

* Product temperature: -40°C to +90°C * Ambient temperature: -25°C to +60°C

Type of support: Slider bed, rollers, PEHD...

MECHANICAL DATA

Tolerances: +20% -10%

Breaking load:200N/mmLoad for 1% extension:13N/mmMaximum working tension:20N/mm

Pulley diameters: (recommended as a minimum with a 20°C ambient temperature)

→

Minimum drive and tension: Ø 60 mm

Minimum reverse flexing: Ø 80 mm

These values are not linked to the requested \emptyset to pull the belt to rotation.

Tél.: +33 (0)4 78 91 81 01

Ambient temperature:

from 0°C to +8°C: add +50% from 0°C to -25°C: add +100%

ENDLESS JOINTINGS

Top heating plate: $160^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Bottom heating plate: $160^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Time: $2 \text{ mn} \pm 1 \text{ mn}$ Pressure: $3,0 \text{ bar } \pm 0,5 \text{ bar}$

Additional material (powder or film): none

These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:


DS (finger joint)



PE (overlap joint)



DS/DEC (double finger joint)



Fasteners: SL02 - Sécura 01 - Sécurinox 1 -

Minibelt - Sécuri G2

Accessories that may be fitted on this belt:

Except for some cases, this belt can be fitted out with a guiding profiles, cleats

sidewalls

These data are subject to modification. Please make sure of their validity. REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France Fax: +33 (0)4 78 91 05 09 www.reveyron.com

E.mail: info@reveyron.fr