# TECHNICAL DATA SHEET



### ISO 9001

### CONVEYOR BELT TPU WHITE

Complies with FDA and EU regulations for conveying of foodstuff

## STANDARD RANGE 2PURB100/FPS

#### CONSTRUCTION

2 2-ply polyester fabric

MAIN TECHNICAL DATA

Top cover:

Total thickness:

Weight per Sq Ft:

- PUR TPU polyurethan
- B Colour : white
- **100** Top cover thickness : 1,00 mm

hardness: 85 Sh.A

Tel.: +33 4 78 91 81 01

Friction Coefficient on steel slider bed:

FPS "Rice grain" positive pattern, easy to clean with sealed ed

surface: mat, smooth

0,134"

0.82 lbs

0,50

± 0,0039 " per ply

± 10%

± 20%


### ENDLESS JOINTINGS

Top heating plate:	329°F	± 20°F
Bottom heating plate:	320°F	± 20°F
Time:	2 mn	± 1 mn
Pressure:	29 psi	± 7 psi
Additional material (powder or film):	none	

These recommendations may vary according to the equipment used and press heating system.

#### Splicing methods to be used:

DS (finger joint)



E.mail: info@reveyron.com

Manufacturing width:	59,06"			
Temperatures: * Product temperature: * Ambient temperature: Type of support:	-40°F to +194°F -13°F to +140°F Slider bed, rollers, PEHD			
	Tolerances: +20% -10%			
Breaking load:	1 028 lbs/in.			
Load for 1% extension:	74 lbs/in.			
Maximum working tension: Pulley diameters:	114 lbs/in. (recommended as a minimum with a 70°F ambient temperature)	Fasteners:	Sécura 02 - Sécurinox 2 - Airport - Gémini	
	Minimum drive and tension: Ø 3,94" Minimum reverse flexing: Ø 6,30"	Accessories that may be fitted on this belt:	Except for some cases, this belt can be fitted out with : guiding profiles, cleats, sidewalls	
These values are not linked to rotation.	o the requested $arnothing$ to pull the belt to			
Ambient temperature: from	32°F to +46°F: add +50%			
from	32°F to -13°F: add +100%			
RE	These data are subject to modification VEYRON S.A. should not be held responsible		•	
reveyron S.A.				

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

www.reveyron.com

Fax: +33 4 78 91 05 09