

# **TECHNICAL DATASHEET**

# STANDARD RANGE 3TV100AS/LW

# DESCRIPTION

- 3 3-ply polyester fabric
- PVC Т
- Colour: green RAL 6004 V
- Top cover thickness: 1,00 mm 100
- AS Antistatic top cover
- 125 N/mm fabric, rigid in weft L
- Impregnated bottomside W

#### MAIN TECHNICAL DATA

Top cover: Hardness 74 ShA Smooth, matte

Total thickness: 4,00 mm ± 0,1 mm per ply

Weight per m<sup>2</sup>: 4 600 g ± 10%

Manufacturing width: 3 000 mm

Temperature range: -5°C à +90°C

Type of support: Slider bed -

Coefficient of friction (on steel slider bed): 0,20 ± 20%

MECHANICAL STRENGTHS Tolerances: -10% +20%


Tensile strength: 300 N/mm

Tensile force for 1% elongation (k1%): 15 N/mm

Maximum working tension: 25 N/mm

#### MINIMUM PULLEY DIAMETERS

(at 20°C ambient temperature)




From -5°C to +8°C: add +50% on min. pulley diameter

The minimum pulley diameter is not related to the diameter needed to achieve a friction drive.


**Conveyor belt PVC BLUE-GREEN** Does not comply with EU regulations for conveying foodstuff

# SPLICING OPTIONS


DS Round finger single splice, 50 x 20 mm



DS/DEC Round finger overlapped splice



SF/PF Straight or Diagonal single overlap splice



# PRESS SETTINGS

These recommendations may vary according to the equipment and press heating system

Top heating platen (± 10°C): 170°C

Bottom heating platen (± 10°C): 170°C

Welding time (± 1 min): 5 min

Pressure (± 0,5 bar): 2,0 bar

Reveyron does not recommend using foil for splicing.

# **FASTENERS / LACING**

Airport-A (steel, rivet) - Airport-I (inox, rivet) - AZ9 (plastic zip) -Flexagraf (plastic) - Gemini-A (inox, rivet) - Gemini-I (inox, rivet) -Minibelt-A (steel, rivet) - Minibelt-I (inox, rivet) - Secura-R5 (inox, round wires) - Securi-P2 (inox, flat wires) - Securi-P3 (inox, flat wires) - SL03 (self-lock, inox) -

# **BELT FABRICATION**

This belt material can be fitted with: V-guides / cleats / corrugated sidewalls /

These data may change. The client remains liable for the proper choice of the belt material. Reveyron cannot be held responsible for any damage caused by improper use of the belt material.

REVEYRON SAS 247 route du Mas Rillier - Les Echets - 01700 MIRIBEL - FRANCE Light Conveyor Belts & Belt Bend Conveyors



Tel: +33 4 78 91 08 51 www.reveyron.com info@reveyron.com VAT FR54 769 201 187 art 286 ter du CGI - Capital 1 000 000 € - Siret 769 201 187 00010 - NAF 1396Z