TECHNICAL DATA SHEET



Validation date: 02/12/2008

ISO 9001

STANDARD RANGE 2PURB40/LHR

CONVEYOR BELT TPU WHITE Complies with FDA and EU regulations for conveying of foodstuff

CONSTRUCTION

- 2-ply polyester fabric 2
- PUR TPU polyurethan
- В Colour : white
- Top cover thickness : 0,40 mm 40
- 125N/mm fabric, rigid in weft L
- "Rice grain" positive pattern, easy to clean HR

MAIN TECHNICAL DATA

hardness: 85 Sh.A Top cover: surface: mat. smooth 0,091" ± 0,0039 " per ply **Total thickness:** Weight per Sq Ft: 0,53 lbs ± 10% DS (finger joint) Friction Coefficient on steel slider bed: 0,50 ± 20% Manufacturing width: 78,74" **Temperatures:** -40°F to +194°F * Product temperature: -13°F to +140°F * Ambient temperature: Slider bed, rollers, PEHD... Type of support: +20% -10% Tolerances: **MECHANICAL DATA** Breaking load: 1 142 lbs/in. lbs/in. Load for 1% extension: 80 Maximum working tension: lbs/in. 114 Fasteners: (recommended as a minimum with a 70°F **Pulley diameters:** ambient temperature) Minimum drive and fitted on this belt: tension: Ø 1,97" Minimum reverse flexing: Ø 2,76"

These values are not linked to the requested Ø to pull the belt to rotation. from 32°F to +46°F: add +50%

Ambient temperature:

from 32°F to -13°F: add +100% These data are subject to modification. Please make sure of their validity.

REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France					
Tel.: +33 4 78 91 81 01	Fax: +33 4 78 91 05 09	www.reveyron.com	E.mail: info@reveyron.com		

ENDLESS JOINTINGS

Top heating plate:	320°F	± 20°F
Bottom heating plate:	320°F	± 20°F
Time:	2 mn	± 1 mn
Pressure:	15 psi	± 7 psi
Additional material (powder or film):	none	

These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:

PE step overlap

DS/DEC (double finger joint)



Accessories that may be





SL02 - Sécura 01 - Sécurinox 1 - Minibelt - Sécuri G2

Except for some cases, this belt can be fitted out with : guiding profiles, cleats, sidewalls